



MASTER UltraEfficient LED bulb

MAS LEDBulbND2.3-40W E27 830 A60 CL G UE

This is the most efficient LED bulb from Philips brand. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only the high SPEC product, but also keep the light quality of Philips brand

Product data

General Information	
Cap-Base	E27
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	485 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	210 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Photobiological safety according to EN 62471 RG1	
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	2.3 W
Lamp Current (Nom)	25 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	70 °C

MASTER UltraEfficient LED bulb

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	A60
Net Weight (Piece)	0.035 kg

Approval and Application

Energy Efficiency Class	A
Energy Consumption kWh/1000 h	3 kWh
EPREL Registration Number	1543851
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

Product Data



Order product name	MAS LEDBulbND2.3-40W E27 830 A60 CL G UE
Full product name	MAS LEDBulbND2.3-40W E27 830 A60 CL G UE
Full product code	872016925404600
Order code	929003702502
Material Nr. (12NC)	929003702502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169254046
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169254053

Dimensional drawing



Product	D	C
MAS LEDBulbND2.3-40W E27 830 A60 CL G UE	60 mm	104 mm

Photometric data




Spectral Power Distribution Colour - MAS LEDBulbND2.3-40W E27 830 A60 CL G UE

Light Distribution Diagram - MAS LEDBulbND2.3-40W E27 830 A60 CL G UE

MASTER UltraEfficient LED bulb


Photometric data




General Uniform Lighting - MAS LEDBulbND2.3-40W E27 830 A60 CL G UE

General uniform lighting - MAS LEDBulbND2.3-40W E27 830 A60 CL G UE

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS LEDBulbND2.3-40W E27 830 A60 CL G UE

