Rittal – The System.

Faster – better – everywhere.

LED system light – SZ 2500.110

Date : Aug 18, 2021

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

LED system light – SZ 2500.110

created: 18.08.2021 on www.rittal.com/com-en



Product description

Design:	Without socket
Benefits:	Optimum illumination of the entire enclosure Optionally with clip, screw and magnetic attachment A configuration to suit every application
Equipment:	Without socket
Material:	Light body: Extruded aluminium Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free)
Colour:	Enclosure: RAL 7016
Protection category IP to IEC 60 529:	IP 20
Supply includes:	Assembly screws
Note:	Connection accessories should be ordered separately

Product description

Dimensions:	Width: 337 mm Height: 55 mm Depth: 23 mm
Rated operating voltage:	100 V - 240 V, 1~, 50 Hz/60 Hz
Installation options:	The internal mounting rail AX and the mounting bracket are required when installing in

	compact enclosures Directly onto the enclosure section with 25 mm pitch pattern
Operating temperature:	Operation (environment): -20 °C...+55 °C
Power consumption:	7 W
Luminous flux:	600 lm
Light colour:	4000 K (neutral white)
Protection class:	II (all-insulated)
Connection options:	Infeed, 2-pole Through-wiring, 2-pole Door-operated switch
Light – installation type:	Screw-fastening Clip attachment Magnetic attachment (accessory)
Packs of:	1 pc(s).
Weight/pack:	0.35 kg
Copper weight (kg per piece):	0
EAN:	4028177806948
Customs tariff number:	94054099
ETIM 7.0:	EC000321
ETIM 6.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 6.0/6.1:	27189241
Product description:	SZ System Light LED, 600 Lumen, L: 337 mm, 100-240 V

Approvals

Approvals:	CCC ENEC
Certificates:	EAC

Declarations:	Declaration of conformity