## Rittal - The System.

Faster – better – everywhere.

## Fan mounting plate for VX IT, TS IT, TE – DK 5502.010

Date : Aug 18, 2021



## Fan mounting plate for VX IT, TS IT, TE – DK 5502.010

created: 18.08.2021 on www.rittal.com/com-en



## Discontinued article.

This item will be discontinued on: 31.12.2021 |||Please note the amended version of the alternative product recommendation:: 5503010

Product description	
Description:	For active ventilation. The unit may optionally be extended with additional fans.
Applications:	For use in the cut-out integrated into the roof plate
Colour:	RAL 7035
Supply includes:	1 fan unit 2 fans 1 thermostat Connection cable, open-ended Assembly parts
Note:	The noise level given refers to the first fan Connection via distributor box or country-specific connector
Product description	
Air throughput per fan (unimpeded air flow):	At 50 Hz: 160 m³/h At 60 Hz: 180 m³/h
Air throughput, unimpeded air flow (without filter mats):	320 m³/h / 360 m³/h
Air throughput, unimpeded air flow (with filter mats):	

© Rittal 2021

Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 200 mm Height: 59 mm Depth: 550 mm
Installation options:	In VX IT with W x D (mm): 600 x 600 / 600 x 800 / 600 x 1000 / 600 x 1200 / 800 x 600 In the TS IT with W x D: 600 x 600 / 600 x 800 / 600 x 1000 / 600 x 1200 / 800 x 600
Temperature range:	Operation (environment): +5 °C+55 °C
Power per fan:	At 50 Hz: 15 W At 60 Hz: 14 W
Noise level:	Per fan: 37 dB(A)
No. of fans:	2
Number of fans (max.):	3
eCl@ss 8.0/8.1:	27189272
Packs of:	1 pc(s).
Weight/pack:	3.5 kg
EAN:	4028177679245
Customs tariff number:	84149000
ETIM 7.0:	EC000331
ETIM 6.0:	EC000331
eCl@ss 8.0/8.1:	27189272
eCl@ss 6.0/6.1:	27400604
Product description:	DK Fan mounting plate, WHD: 200x59x550 mm, max. 3 fans, For TS IT, RAL 7035
Approvals	
Approvals:	Approval overview
Certificates:	EAC

© Rittal 2021 2