Rittal – The System.

Faster - better - everywhere.


Compact enclosure AX Basic enclosure AX, sheet steel – AX 1115.000

Date : Aug 18, 202



Compact enclosure AX Basic enclosure AX, sheet steel – AX 1115.000

created: 18.08.2021 on www.rittal.com/com-en



Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 1, 12
Type rating to UL 50E:	Type 1, 12
IK Code:	IK10
Supply includes:	Enclosure with door(s) Gland plate(s) in enclosure base Mounting plate Perforated door strip Lock: 3 mm double-bit
Basic material:	Sheet steel

Height: 1400 mm

Width: 1000 mm

Dimensions:

Depth: 400 mm

Material thickness: Enclosure: 1.5 mm

Door: 2 mm

Mounting plate: 2.5 mm

Mounting plate: Width: 945 mm

Height: 1375 mm

Number of doors: 2

Door hinged on the right, may be swapped to the left:

yes

3-point lock system: yes

Lock version: 3-point lock system

Number of locks: 1

Lock insert: 3 mm double-bit

Gland plate, size: 6

Gland plate, qty.: 2

Packs of: 1 pc(s).

Weight/pack: 100 kg

EAN: 4028177813083

Customs tariff number:

94032080

ETIM 7.0: EC000261

ETIM 6.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 6.0/6.1: 27180101

Product description: AX Compact enclosure, WHD: 1000x1400x400 mm, sheet steel, with mounting plate,

two-door, with 3-point lock system

Approvals

Approvals: Bureau Veritas

© Rittal 2021 2

DNV-GL Lloyds Register of Shipping UL + C-UL

Certificates:	Certificate of manufacturer according to RMRS Protection category
Declarations:	Declaration of conformity

© Rittal 2021 3