## Rittal - The System.

Faster – better – everywhere.

Hygienic Design Compact enclosure HD, single-door – HD 1314.600

Date : Aug 18, 2021



## Hygienic Design Compact enclosure HD, single-door – HD 1314.600

created: 18.08.2021 on www.rittal.com/com-en



Design:	Roof angled forwards by 30°			
Material:	Enclosure and door: Stainless steel 1.4301 (AISI 304)			
	Mounting plate: Sheet steel Lock insert HD: Stainless steel 1.4404 (AISI 316L)			
	Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600			
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 μm			
	Mounting plate: Zinc-plated Seal: Blue, dyed (RAL 5010)			
	Seal. Blue, dyed (RAL 5010)			
Protection category	IP 66			
IP to IEC 60 529:	IP X9			
Protection category IP to DIN 40 050-9:	IP 69K			
Protection category NEMA:	NEMA 13 NEMA 4X			
NEWA.	NEWA 4A			
IK Code:	IK08			
Supply includes:	Enclosure of all-round solid construction			
	Door with inserted seal			
	Door hinged on the right, may be swapped to the left Mounting plate			
Product modification:	From June 2020, the compact enclosure HD, single-door, comes with the new compact enclosure AX mounting plate.			

© Rittal 2021

Drod	14	ممه	arin	tion
Prod	uct	aes	CLID	uon

Dimensions: Width: 810 mm

Height (front): 430 mm Height rear: 549 mm Depth: 210 mm

Mounting plate: Width: 750 mm

Height: 355 mm

Door opening angle: 125°

Number of cam locks: 2

Packs of: 1 pc(s).

Weight/pack: 25.5 kg

**EAN**: 4028177815674

Customs tariff number:

94032080

**ETIM 7.0**: EC000261

**ETIM 6.0:** EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 6.0/6.1: 27180101

Product description: HD Compact enclosure, WHD: 810x430(H1)x549(H2)x210 mm, Stainless steel 1.4301,

with mounting plate, with hinged door and silicone seal

## **Approvals**

Approvals: UL + C-UL

Certificates: NA

Protection category

**Declarations:** Declaration of conformity