

Rittal – The System.

Faster – better – everywhere.

► Hygienic Design Compact enclosure HD, single-door – HD 1315.600

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygienic Design Compact enclosure HD, single-door – HD 1315.600

created: 18.08.2021 on www.rittal.com/com-en



Product description

Design:	Roof angled forwards by 30°
Material:	Enclosure and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Sheet steel Lock insert HD: Stainless steel 1.4404 (AISI 316L) Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated Seal: Blue, dyed (RAL 5010)
Protection category IP to IEC 60 529:	IP 66 IP X9
Protection category IP to DIN 40 050-9:	IP 69K
Protection category NEMA:	NEMA 13 NEMA 4X
IK Code:	IK08
Supply includes:	Enclosure of all-round solid construction Door with inserted seal Door hinged on the right, may be swapped to the left Mounting plate
Product modification:	From June 2020, the compact enclosure HD, single-door, comes with the new compact enclosure AX mounting plate.

Basic material: Stainless steel

Product description

Dimensions: Width: 810 mm
Height (front): 650 mm
Height rear: 821 mm
Depth: 300 mm

Mounting plate: Width: 750 mm
Height: 575 mm

Door opening angle: 125°

Number of cam locks: 2

Packs of: 1 pc(s).

Weight/pack: 39 kg

EAN: 4028177815667

Customs tariff number: 94032080

ETIM 7.0: EC000261

ETIM 6.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 6.0/6.1: 27180101

Product description: HD Compact enclosure, WHD: 810x650(H1)x821(H2)x300 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal

Approvals

Approvals: UL + C-UL

Certificates: NA
Protection category

Declarations: Declaration of conformity