

# Rittal – The System.

Faster – better – everywhere.

## Punched section with mounting flange, 23 x 64 mm for VX, VX IT, VX SE, AX plastic – VX 8617.150

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Punched section with mounting flange, 23 x 64 mm for VX, VX IT, VX SE, AX plastic – VX 8617.150

created: 18.08.2021 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



Product description	
Description:	For variable, individual interior installation.
Benefits:	Simply locate into the system punchings and screw-fasten System punchings on all four sides With slots at the top and bottom for cage nuts, for attaching your own components via metric screws
Material:	Sheet steel
Surface finish:	Zinc-plated
Supply includes:	Assembly parts
Product description	
To fit:	Enclosure type: VX Enclosure type: VX IT Enclosure type: VX SE Enclosure type: AX plastic Width/height/depth: 1000 mm
Installation options:	In VX, VX IT on the inner mounting mounting level, on the enclosure section VX In the VX SE, on the VX SE enclosure section in conjunction with the VX adaptor rail In AX plastic in the enclosure height/width in conjunction with universal brackets On identical punched sections with mounting flanges In base/plinth system VX in the width and depth, combined with a base/plinth installation bracket
Packs of:	4 pc(s).

<b>Weight/pack:</b>	4.22 kg
<b>Copper weight (kg per piece):</b>	0
<b>EAN:</b>	4028177829152
<b>Customs tariff number:</b>	94039010
<b>ETIM 7.0:</b>	EC002625
<b>ETIM 6.0:</b>	EC002625
<b>eCl@ss 8.0/8.1:</b>	27189234
<b>eCl@ss 6.0/6.1:</b>	23159101
<b>Product description:</b>	VX Punched section, with mounting flange 23 x 64 mm, for inner mounting level