

Rittal – The System.

Faster – better – everywhere.

► **Network/server rack
VX IT with glazed
door, IP 55, with 482.6
mm (19") mounting
angles, standard – VX
5303.134**

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network/server rack VX IT with glazed door, IP 55, with 482.6 mm (19") mounting angles, standard – VX 5303.134

created: 18.08.2021 on www.rittal.com/com-en



Product description

Material:	Sheet steel Aluminium Glazed door: Single-pane safety glass, 3 mm
Surface finish:	Enclosure frame: Dipcoat-primed Interior installation: Spray-finished Rear door and roof: Dipcoat-primed, powder-coated Front door: Aluminium, anodised/spray-finished
Colour:	Enclosure frame, rear door and roof: RAL 7035 Front door: Vertical sections, silver coloured and horizontal sections, RAL 9005 Interior installation: RAL 9005 Handle and hinges: RAL 9005
Protection category IP to IEC 60 529:	IP 55 only in conjunction with baying seal or screw-fastened side panels
Supply includes:	VX enclosure frame with doors and roof plate Glazed aluminium door at the front, 180° hinges Sheet steel rear door, solid, one-piece, 130° hinges Lock front and rear: Comfort handle for profile half-cylinders and security lock 3524 E Mounting angles, 482.6 mm (19") Roof plate, one-piece, solid Base tray with gland plate, multi-piece, solid Baying seal and sealing kit for gland plates (supplied loose) 12 x 482.6 mm (19") fastener, 1 U, conductive (supplied loose) 25 multi-tooth screws, conductive (supplied loose) IPPC pallet
Note:	Depending on how and where it is sited, the door opening angle may vary for selected applications

Basic material:	Sheet steel
Product description	
Dimensions:	Width: 800 mm Height: 1200 mm Depth: 800 mm
Installation height for components:	24 U
Distance between levels as delivered:	520 mm
482.6 mm (19") version:	front and rear
482.6 mm (19") attachment:	on the cross-member, screw-fastened at the top and bottom
Free mounting space to the 482.6 mm (19") level, front/rear:	150 mm / 130 mm
Load capacity:	8000 N Static (max.) per enclosure to UL 2416: 8000 N
Packs of:	1 pc(s).
Weight/pack:	90.8 kg
EAN:	4028177944855
Customs tariff number:	94032080
ETIM 7.0:	EC002499
ETIM 6.0:	EC002499
eCl@ss 8.0/8.1:	27180207
eCl@ss 6.0/6.1:	27180207
Product description:	VX IT, 19" mounting angles, standard, front and rear, glazed door, WHD: 800 x 1200 x 800 mm, 24 HE, IP 55
Approvals	
Approvals:	UL + C-UL
Certificates:	Protection category IP 55 (CPRI)

Declarations:

Declaration of conformity
