

# Rittal – The System.

Faster – better – everywhere.

## **Network/server rack VX IT with vented doors, with 482.6 mm (19") mounting angles, standard – VX 5303.114**

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Network/server rack VX IT with vented doors, with 482.6 mm (19") mounting angles, standard – VX 5303.114

created: 18.08.2021 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Material:</b>	Sheet steel Aluminium
<b>Surface finish:</b>	Enclosure frame: Dipcoat-primed Interior installation: Spray-finished Rear door and roof: Dipcoat-primed, powder-coated Front door: Aluminium, anodised/spray-finished
<b>Colour:</b>	Enclosure frame, rear door and roof: RAL 7035 Front door: Vertical sections, silver coloured and horizontal sections, RAL 9005 Interior installation, vent grille at the front: RAL 9005 Handle and hinges: RAL 9005
<b>Supply includes:</b>	VX enclosure frame with doors and roof plate Aluminium/sheet steel door at the front, vented (vented surface area approx. 85% perforated), 180° hinges Sheet steel rear door, vented (vented surface area approx. 85% perforated) Lock front and rear: Comfort handle for profile half-cylinders and security lock 3524 E Mounting angles, 482.6 mm (19") Spacers, height 50 mm, to raise a cover plate above the fan cut-out in the roof plate, for passive cooling (supplied loose). Not required for variants without a cut-out. 12 x 482.6 mm (19") fastener, 1 U, conductive (supplied loose) 25 multi-tooth screws, conductive (supplied loose) IPPC pallet Sheet steel door, vented, one-piece, 130° hinges Roof plate, multi-piece, with side cable entry in the depth, double-sided, prepared for fan mounting plate
<b>Note:</b>	Depending on how and where it is sited, the door opening angle may vary for selected applications
<b>Basic material:</b>	Sheet steel

## Product description

<b>Dimensions:</b>	Width: 800 mm Height: 1200 mm Depth: 800 mm
<b>Installation height for components:</b>	24 U
<b>Distance between levels as delivered:</b>	520 mm
<b>482.6 mm (19") version:</b>	front and rear
<b>482.6 mm (19") attachment:</b>	on the cross-member, screw-fastened at the top and bottom
<b>Free mounting space to the 482.6 mm (19") level, front/rear:</b>	150 mm / 130 mm
<b>Load capacity:</b>	8000 N Static (max.) per enclosure to UL 2416: 8000 N
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	67.5 kg
<b>EAN:</b>	4028177944831
<b>Customs tariff number:</b>	94032080
<b>ETIM 7.0:</b>	EC011217
<b>ETIM 6.0:</b>	EC002499
<b>eCl@ss 8.0/8.1:</b>	27180207
<b>eCl@ss 6.0/6.1:</b>	27180207
<b>Product description:</b>	VX IT, 19" mounting angles, standard, front and rear, vented, WHD: 800 x 1200 x 800 mm, 24 U

## Approvals

<b>Approvals:</b>	UL + C-UL
<b>Declarations:</b>	Declaration of conformity