

# Rittal – The System.

Faster – better – everywhere.

## **Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7709.535**

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7709.535

created: 18.08.2021 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Design:</b>	Pre-configured
<b>Description:</b>	Wall-mounted enclosure with optimum accessibility due to hinged part.
<b>Material:</b>	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
<b>Surface finish:</b>	Powder-coated
<b>Colour:</b>	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
<b>Protection category IP to IEC 60 529:</b>	IP 54 in conjunction with solid gland plate, top and bottom
<b>IK Code:</b>	IK08
<b>Supply includes:</b>	Wall section with solid gland plate at the top and brush strip at the bottom, two vertical mounting rails and C rail, horizontal, for cable clamping Hinged part with 25 mm pitch pattern of holes in the front and rear frame, two 482.6 mm (19") mounting angles at the front, infinitely depth-variable, and side outlet filters on the left and right Earth rail with star earthing Designer glazed door 1 double-kit key no. 5 Wall mounting bracket, 10 mm, reinforced Mini-comfort handle for lock inserts Security lock 3524 E
<b>Basic material:</b>	Sheet steel

## Product description

**Dimensions:** Width: 600 mm  
Height: 478 mm  
Units: 9 U  
Depth: 673 mm

**Depth hinged part:** 516 mm

**Installation depth:** 620 mm

**Clearances:** Clearance width: 502 mm  
Clearance height: 415 mm

**Wall section:** Depth: 135 mm

**Load capacity:** Hinged part, static (max.): 450 N

**Packs of:** 1 pc(s).

**Weight/pack:** 38 kg

**EAN:** 4028177551015

**Customs tariff number:** 94032080

**ETIM 7.0:** EC000261

**ETIM 6.0:** EC000261

**eCl@ss 8.0/8.1:** 27142408

**eCl@ss 6.0/6.1:** 27180208

**Product description:** DK Wall-mounted enclosures, 3-part, WHD: 600x478x673 mm, 9 U, Pre-configured, with mounting angles, depth-variable

## Approvals

**Approvals:** UL + C-UL

**Certificates:** IK-Code  
NA  
Protection category

**Declarations:** Declaration of conformity