

Rittal – The System.

Faster – better – everywhere.

Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.535

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.535

created: 18.08.2021 on www.rittal.com/com-en



Product description	
Design:	Pre-configured
Description:	Wall-mounted enclosure with optimum accessibility due to hinged part.
Material:	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Colour:	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
Protection category IP to IEC 60 529:	IP 54 in conjunction with solid gland plate, top and bottom
IK Code:	IK08
Supply includes:	Wall section with solid gland plate at the top and brush strip at the bottom, two vertical mounting rails and C rail, horizontal, for cable clamping Hinged part with 25 mm pitch pattern of holes in the front and rear frame, two 482.6 mm (19") mounting angles at the front, infinitely depth-variable, and side outlet filters on the left and right Earth rail with star earthing Designer glazed door 1 double-kit key no. 5 Wall mounting bracket, 10 mm, reinforced Mini-comfort handle for lock inserts Security lock 3524 E
Basic material:	Sheet steel

Product description

Dimensions: Width: 600 mm
Height: 746 mm
Units: 15 U
Depth: 673 mm

Depth hinged part: 516 mm

Installation depth: 620 mm

Clearances: Clearance width: 502 mm
Clearance height: 683 mm

Wall section: Depth: 135 mm

Load capacity: Hinged part, static (max.): 750 N

Packs of: 1 pc(s).

Weight/pack: 48 kg

EAN: 4028177551022

Customs tariff number: 94032080

ETIM 7.0: EC000261

ETIM 6.0: EC000261

eCl@ss 8.0/8.1: 27142408

eCl@ss 6.0/6.1: 27180208

Product description: DK Wall-mounted enclosures, 3-part, WHD: 600x746x673 mm, 15 U, Pre-configured, with mounting angles, depth-variable

Approvals

Approvals: UL + C-UL

Certificates: IK-Code
NA
Protection category

Declarations: Declaration of conformity