

# Rittal – The System.

Faster – better – everywhere.

## ► Baying enclosure system VX25 Basic enclosure – VX 8865.000

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Baying enclosure system VX25 Basic enclosure – VX 8865.000

created: 18.08.2021 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

|                                                  |                                                                                                                                                                                                               |
|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Material:</b>                                 | Enclosure frame: Sheet steel, 1.5 mm<br>Roof: Sheet steel, 1.5 mm<br>Door: Sheet steel, 2.0 mm<br>Rear panel: Sheet steel, 1.5 mm<br>Gland plates: Sheet steel, 1.5 mm<br>Mounting plate: Sheet steel, 3.0 mm |
| <b>Surface finish:</b>                           | Enclosure frame: Dipcoat-primed<br>Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint<br>Mounting plate and gland plates: Zinc-plated                                    |
| <b>Colour:</b>                                   | RAL 7035                                                                                                                                                                                                      |
| <b>Protection category<br/>IP to IEC 60 529:</b> | IP 55                                                                                                                                                                                                         |
| <b>Protection category<br/>NEMA:</b>             | NEMA 1, 12                                                                                                                                                                                                    |
| <b>Type rating to UL 50E:</b>                    | Type 1, 12                                                                                                                                                                                                    |
| <b>IK Code:</b>                                  | IK10                                                                                                                                                                                                          |
| <b>Supply includes:</b>                          | Enclosure frame<br>Door(s)<br>Door hinged on the right, may be swapped to the left<br>Roof plate<br>Rear panel<br>Gland plates<br>Mounting plate<br>2 punched rails 18 x 39 mm<br>Lock: 3 mm double-bit       |

**Basic material:** Sheet steel

## Product description

**Dimensions:** Width: 800 mm  
Height: 1600 mm  
Depth: 500 mm

**Mounting plate:** Width: 699 mm  
Height: 1496 mm

**Number of doors:** 1

**Packs of:** 1 pc(s).

**Weight/pack:** 102 kg

**EAN:** 4028177813892

**Customs tariff number:** 94032080

**ETIM 7.0:** EC000261

**ETIM 6.0:** EC000261

**eCl@ss 8.0/8.1:** 27180101

**eCl@ss 6.0/6.1:** 27180101

**Product description:** VX Baying enclosure system, WHD: 800x1600x500 mm, sheet steel, with mounting plate, single door at the front

## Approvals

**Approvals:** Bureau Veritas  
CCC exception letter  
DNV-GL  
Lloyds Register of Shipping  
UL + C-UL

**Certificates:** Certificate of manufacturer according to RMRS  
NA  
Protection category

**Declarations:** Declaration of conformity