Rittal - The System.

Faster – better – everywhere.


Compact enclosure AX Basic enclosure AX, sheet steel – AX 1260.000

Date : Aug 18, 2021



Compact enclosure AX Basic enclosure AX, sheet steel - AX 1260.000

created: 18.08.2021 on www.rittal.com/com-en



Product description	
Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 1, 3R, 4, 12
Type rating to UL 50E:	Type 1, 3R, 4, 12
IK Code:	IK10
Supply includes:	Enclosure with door(s) Gland plate(s) in enclosure base Mounting plate Perforated door strip Lock: 3 mm double-bit
Basic material:	Sheet steel

Dimensions: Width: 600 mm Height: 1200 mm

© Rittal 2021

Depth: 300 mm

Material thickness: Enclosure: 1.5 mm

Door: 2 mm

Mounting plate: 2.5 mm

Mounting plate: Width: 545 mm

Height: 1175 mm

Number of doors: 1

Door hinged on the right, may be swapped to the left:

yes

3-point lock system: yes

Lock version: 3-point lock system

Number of locks: 1

Lock insert: 3 mm double-bit

Gland plate, size: 7

Gland plate, qty.: 1

Packs of: 1 pc(s).

Weight/pack: 50 kg

EAN: 4028177813274

Customs tariff number:

94032080

ETIM 7.0: EC000261

ETIM 6.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 6.0/6.1: 27180101

Product description: AX Compact enclosure, WHD: 600x1200x300 mm, sheet steel, with mounting plate,

single-door, with 3-point lock system

Approvals

Approvals: Bureau Veritas

DNV-GL Lloyds Register of Shipping UL + C-UL

Certificates:	Certificate of manufacturer according to RMRS Protection category
Declarations:	Declaration of conformity

© Rittal 2021 3