

Rittal – The System.

Faster – better – everywhere.

Rail for interior installation AX – AX 2393.300

Date : Aug 18, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Rail for interior installation AX – AX 2393.300

created: 18.08.2021 on www.rittal.com/com-en



Product description

Description:	For mounting in the enclosure, no machining required. Suitable for mounting on the side, base and roof up to a load of 25 N using the locators integrated into the enclosure lights, door-operated switch, door stay, cable conduit holder enclosure. Variable with 2 rows of system punchings, creates additional mounting space e.g. for: Punched section with mounting flange 14 x 39 mm, enclosure lights, door-operated switch, door stay, cable conduit holder.
Benefits:	Only one screw for attaching the rail inside the enclosure Including adaptor for door-operated switch Compatibility with VX25 accessories Enclosure protection category is retained (no machining required) Automatic potential equalisation May be retro-fitted even with the mounting plate in situ. Suitable for installation via gland plates
Material:	Sheet steel
Surface finish:	Zinc-plated
Assembly instruction:	For installing LED system light, only in conjunction with mounting bracket for interior installation

Product description

To fit:	Enclosure type: AX Depth: = 300 mm
Packs of:	4 pc(s).
Weight/pack:	0.7 kg

Copper weight (kg per piece):	0
EAN:	4028177925229
Customs tariff number:	73269098
ETIM 7.0:	EC002625
ETIM 6.0:	EC002625
eCl@ss 8.0/8.1:	27189234
eCl@ss 6.0/6.1:	23159101
Product description:	AX Rail for interior installation, for D: 300 mm