CAT. N° 0 371 73



TERMINAL BLOCK VIKING 3 -SCREW -FR CONDUCTOR -1 CONNECTION -METAL BASE -PITCH 10

Pack (number of units)	30
Volume (dm³)	1,256
Weight (g)	871,00

Product characteristics

For protection conductor

- Metal base

1 connection - 1 entry/1 outlet

- Screwless fixing on rail up to 10 mm pitch and with screws for pitch 12 and 15 mm
- PEN from 10 mm²
- Colour : Green/yellow
- Nominal cross-section : 10 mm²
- Capacity – Rigid wire : 1.5 to 16 mm²
- Capacity – Flexible wire with or without ferrules : 2.5 to 10 mm²
- Pitch : 10 mm

General characteristics

Viking™ 3 terminal blocks with screw connection - for copper cables

- Used to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires
- 2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)
- For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Documentation

Catalogue pages & additional information

- Selection chart (p.324-325)
- Description page (p.328)
- Technical page (p.335)
- VikingTM 3 terminal blocks with screw connection

Agreements & certificates of conformity

- IMQ - CA02.03545
- Ex - 002/G
- NF App Industri - NF208_1008
- UL recogn - 20101029-E60900
- ATEX - LCIE 16 ATEX 3049U - 02

Installation & technical data

- F00671EN-02
- F00914EN-00
- F00914EN-01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.