



### 3-pole, 32A Modular Switch

#### Technical Characteristics

|   |   |
|---|---|
| Neutral position  | without neutral                                 |
| Number of poles   | 3 P   |
| Type of pole  | 3 P   |
| Rated operational voltage Ue                                      | 400 V   |
| Frequency   | 50/60 Hz  |
| Rated current   | 32 A  |
| Rated insulation voltage  | 440 V   |
| Rated impulse withstand voltage                                   | 4000 V  |
| Depth of installed product  | 68 mm   |
| Height of installed product                                       | 83 mm   |
| Width of installed product  | 35 mm   |
| Total power loss under IN   | 4.5 W   |
| Electrical durability at nominal load in AC22 in operating cycles | 25000   |
| Number of mechanical operations                                   | 200000  |
| Number of modules   | 2   |
| Tightening torque   | 1,8Nm   |
| Connection cross-sect. flexible conductor                         | 1,5 / 10mm <sup>2</sup>                         |
| Connection cross-sect. rigid cable                                | 1,5 / 16mm <sup>2</sup>                         |
| Type of connection  | with screw                                      |
| Standard text   | IEC 60947-3<br>IEC/EN 60669-2<br>IEC/EN 60669-4 |
| European directive WEEE   | concerned                                       |
| Protection index IP   | IP20  |
| Operating temperature   | -20...50 °C                                     |