
Item no.: 1020923



LED spotlights theLeda S

Description

- LED spotlight with motion detector
- 2 LED spot with 10 W each (equivalent to 2x140 W Halogen spotlight)
- Spotlights can be swivelled $\pm~20^{\circ}$ horizontally, and adjusted 70° downwards
- Suitable for outdoor use
- Automatic lighting control based on presence and brightness
- 180° detection angle at a detection range of 10 m
- Area limit via lens attachment
- Orientation light with configurable dimming level
- Short and extended function via manual control system
- Integrated heat sink in housing color
- Direct-LED for maximum light output
- High-tech matrix-LED module
- Single-handed plug-in installation
- Instant start-up possible via factory preset
- Adjustable lux value and switch-off delay
- Settings can be changed without tools



Technical data


	theLeda S20 WH	
Operating voltage	230 V AC	
Frequency	50 – 60 Hz	
Stand-by consumption	~0.4 W	
Colour	White	
Installation type	Wall installation	
Setting range brightness	5 – 200 lx	
LED output (lighting current)	2 x 840 lm	
Colour temperature	4000 K, neutral white	


	theLeda S20 WH	
Detection angle	180°	
Installation height	1.8 – 2.5 m	
Light switch-off delay	2 s-30 min	
Ambient temperature	-20°C 45°C	
Protection class	I	
Type of protection	IP 55	


Item no.: 1020923



Connection example








Detection range for planning applications


Mounting height (A)	Diagonally (t)	Head on to (R)
2.5 m	10 m	3.5 m

Item no.: 1020923





Detection range for planning applications





Scale drawings





Item no.: 1020923



Accessories

Corner angle 10 WH Item no.: 9070969



Spacer 10 WH Item no.: 9070971

