

ENSTO

Atšakojimo gnybtas

SL37.2

Tipas	SL37.2
GTIN	6418677414411
Pavadinimas	Atšakojimo gnybtas Al 10-95 mm ² ir Al 10-95 mm ²
Aprašymas	Atšakojimo gnybtas SL 37.2 skirtas aliuminio laidininkams sujungti, be mechaninio itempimo. Gnybtas yra su dviem M8 varžtais.

Gamintojas



Techninė specifikacija

Certificates

Standartinis žymėjimas: EN 61238-1

Dimensions

Pagrindinis laidininkas mm²: Al 10-95
 Atšakos laidininkas mm²: Al 10-95
 Laidininko skersmuo mm: 3-13 / 3.5-13
 Net Weight: 0,104 kg

Features

Varžtas: 2xM8
 Plastikinis gaubtas: SP15

Mechanical

Užveržimo momentas: 22 Nm

Others

ETIM Class: EC001062

ETIM Techninė specifikacija

etim

Nominal cross section main conductor SE: 10 ... 95 mm²

Nominal cross section main conductor SM:	10 ... 95 mm ²
Nominal cross section branch conductor SE/RE:	10 ... 95 mm ²
Nominal cross section branch conductor SM/RM:	10 ... 95 mm ²
Material main conductor:	Aluminium
Material branch conductor:	Aluminium
Terminal insulated:	No
Clamping channel opening main conductor:	Both sides open
Clamping channel opening branch conductor:	Both sides open
Surface protection:	Bare
Type of connection:	Screwed connection

Packaging

Pallet package

Unit:	pcs
Package size:	3500
Depth:	1200 mm
Width:	800 mm
Height:	840 mm

Default package

Unit:	pcs
Package size:	50
Depth:	218 mm
Width:	218 mm
Height:	176 mm
Weight:	5,377 kg
Volume:	8,364224 l