

ENSTO

Izoliuojantis gaubtas

SP15



Tipas	SP15
GTIN	6418677405211
Pavadinimas	Izoliuojantis gaubtas Maks. 120 mm ²
Aprašymas	Gaubtas SP15 skirtas gnybto apsaugai. Jis turi būti sumontuotas taip, kad kondensato nutekėjimo skylutės būtų nukreiptos žemyn. Pagamintas iš UV spinduliams ir atmosferos poveikiui atsparaus termoplastiko. Tinka SM2.1, SM2.11, SM2.2, SM2.21, SM2.25, SL4.2, SL4.21, SL4.25, SL4.26, SL37.1, SL37.2 gnybtams.

Gamintojas

Techninė specifikacija

Dimensions

Laidininko matmuo:	≤ 150 mm ²
Net Weight:	0,031 kg

Features

Gnybtui/sujungikliui:	SM2.xx, SL3.xx, SL4.xx, SL37.xx, SL39.xx
-----------------------	--

Others

ETIM Class:	EC000437
-------------	----------

ETIM Techninė specifikacija

etim

Height:	71,5 mm
Type of housing:	Socket case
Material housing:	Plastic
Coating housing:	Uncoated
Position cable feed:	Two-sided

With hinged lid:	Yes
Locking mechanism:	Push Pull
Corrosion resistant:	Yes
UV resistant:	Yes
Degree of protection (IP) mounted:	IP20

Packaging

Pallet package

Unit:	PCE
Package size:	1800
Depth:	1200 mm
Width:	800 mm
Height:	1150 mm

Default package

Unit:	PCE
Package size:	100
Depth:	400 mm
Width:	400 mm
Height:	330 mm
Weight:	3,1 kg
Volume:	52,8 l