

ENSTO

Kombinuotas termostatas

ECO16BT-IM-083



Tipas	ECO16BT-IM-083
GTIN	6438100339036
Pavadinimas	Kombinuotas termostatas ECO Combination thermostat 16A/3600W. Temperature range +5...+50°C / +5...+35°C. NTC-sensor 4m, 47kohm/25°C. Impressivo, aluminum. Double pole switch.IP30
Aprašymas	Ecodesign-compatible combination thermostat for underfloor heating. Options for heating mode are floor or room temperature as well as power. Thermostat is possible to adjust from the knob in device or with downloadable Bluetooth-application (Android and iOS). Main features are calendar, boost, and vacation. Energy consumption can be easily monitored from the app
Gamintojas	Ensto Building Systems Finland Oy

Techninė specifikacija

Dimensions

Ilgis:	48 mm
Matmenys i x p x a:	48 x 85 x 85 mm
Plotis:	85 mm
Aukštis:	85 mm
Net Weight:	0,146 kg

Electrical values

Galia:	3600 W
Nominali įtampa:	230 ... 230 V
Nominali srovė:	16 A
Darbinis dažnis:	50 Hz

Ratings

Apsaugos klasė:	IP30
Protection class:	II

Others

ETIM Class:	EC011309
-------------	----------

ETIM Techninė specifikacija

etim

Type of power supply:	230 V
Connection:	Wireless
With receiver:	Yes
External sensor:	Yes
With thermal feedback:	Yes
Control characteristic:	Other
Heating:	Yes
Number of heater outputs:	1
Number of cooler outputs:	0
Differential value:	≥ 1 K
Adjustable differential:	No
Selector switch for heating and heating with hot water:	No
Sensor/feeler type:	Resistance sensor
Temperature readable:	Yes
With display:	No
Type of clock:	Week clock
Clock model:	Digital
Overtime switch:	No
Optimisation:	Yes
With tap water circuit:	No
Operation:	Turn
Weather-dependent control system:	No
Number of switching programmes:	10
Max. contact voltage:	253 V
Max. contact load:	16 A
Degree of protection (IP):	IP30
Degree of protection (NEMA):	2
Explosion-proof:	No
Colour:	Other
Width:	85 mm
Depth:	48 mm
Height:	85 mm
Class of the temperature control:	II
Standby power consumption (solstandby):	0,5 W

Packaging

Pallet package

Unit:	PCE
Package size:	540
Depth:	1200 mm
Width:	800 mm
Height:	1015 mm

Default package

Unit:	PCE
Package size:	1
Depth:	122 mm
Width:	104 mm
Height:	64 mm
Weight:	0,18 kg
Volume:	0,812032 l