

ENSTO

Atšakinis gnybtas

SLW25.22

Tipas	SLW25.22
GTIN	6438100304218
Pavadinimas	Atšakinis gnybtas OLA (35)50-157 / (35)50-157 AlMgSi
Aprašymas	Gnybtas SLW25.22 yra su nulužtanciomis varžtu galvutėmis ir suteptas pasta. Skirtas vidutinės įtampos iki 36 kV OLA sujungti, nenuėmus apvalkalo, be mechaninės apkrovos. Gnybto dantys dengti nelaidžiu vandeniui silikono tepalu. Nominalus laidininko apvalkalo storis 2,3-3,3 mm. Komplekte yra gaubtas SP16.

Gamintojas



Techninė specifikacija

Certificates

Standartinis žymėjimas:	EN 50397-2:2009
-------------------------	-----------------

Dimensions

Pagrindinis laidininkas mm²:	50-157 AlMgSi
Atšakos laidininkas mm²:	50-157 AlMgSi
Laidininko skersmuo:	12,7 ... 22,3 mm
Net Weight:	0,246 kg

Features

Varžtas:	2 x M10
Plastikinis gaubtas:	SP16

Mechanical

Užveržimo momentas:	42 Nm
---------------------	-------

Others

ETIM Class:	EC001062
-------------	----------

ETIM Techninė specifikacija

etim

Nominal cross section main conductor SM:	50 ... 157 mm ²
Nominal cross section branch conductor SE/RE:	50 ... 157 mm ²
Nominal cross section branch conductor SM/RM:	50 ... 157 mm ²
Material main conductor:	Aluminium
Material branch conductor:	Aluminium
Terminal insulated:	Yes
Clamping channel opening main conductor:	Both sides open
Clamping channel opening branch conductor:	Both sides open
Surface protection:	Bare
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	640
Depth:	1200 mm
Width:	800 mm
Height:	1100 mm

Default package

Unit:	PCE
Package size:	20
Depth:	400 mm
Width:	295 mm
Height:	240 mm
Weight:	4,92 kg
Volume:	28,32 l