
PRODUCT CARD

2021-08-20

ENSTO

Kirtiklių-saugiklių blokas

SZ160.32



Tipas	SZ160.32
GTIN	6438100318321
Pavadinimas	Kirtiklių-saugiklių blokas Saugikliu gabaritas 00 pagal IEC 600269-2A.
Aprašymas	Stulpinis kirtiklis-saugiklis turi atskirus dangtelius ieinantiems ir išeinantiems laidininkams, tai leidžia saugiau prijungti laidininkus. Komplekte yra gnybtai 7 x KG45.5, 3 fazems +PEN.
Gamintojas	

Techninė specifikacija

Certificates

Standartinis žymėjimas:	IEC 60947-3

Dimensions

Laidininko skerspjūvis Al:	16 ... 120 mm²
Laidininko skerspjūvis Cu:	16 ... 120 mm²
Net Weight:	4,08 kg

Electrical values

Fuse:	160 A
Nominal insulation voltage:	1000 V
Nominali įtampa (Un):	≥ 0,415 kV
Nominalios vertės:	160 A, 415 V

Features

Su sujungikliais:	6 x KG45.5 + 1 x KG45
Saugiklio kontaktas:	Not included
Polių skaičius:	3+PEN
Utilizavimo kategorija:	AC22B

Ratings

Apsaugos klasė:	IP23

Short-circuit characteristics

Rated conditional short-circuit current:	50 kA

Others

ETIM Class:	EC001040

ETIM Techninė specifikacija

etim

Max. rated operation voltage Ue AC:	415 V
Rated permanent current Iu:	160 A
Conditioned rated short-circuit current Iq:	50 kA
Suitable for fuses:	NH00
Type of electrical connection of main circuit:	Cable clamp
Cable entry:	Side
Equipped with connectors:	Yes
Type of control element:	Long turning handle

Packaging

Pallet package

Unit:	pcs
Package size:	48
Depth:	1200 mm
Width:	800 mm
Height:	980 mm

Default package

Unit:	PCE
Package size:	1
Depth:	280 mm
Width:	275 mm
Height:	175 mm
Weight:	4,082 kg
Volume:	13,475 l