


CASTOR LED

Diffuser and wall luminaires



Images for the product family and options:



Description:

Surface mounted LED luminaire
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser
 Housing: steel
 Colour: white, RAL 9016

General data:

Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 100000/L70B50
 SDCM: 6
 Protection class IEC: I
 Ingress protection code: IP40
 Mechanical impact resistance: IK06
 Operating temperature range, °C: ta -20...+40

Installation:

On the ceiling or wall. Push-in terminals, 3x2x2.5mm²

Environment:

Indoor

Application:

Office, education, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Castor LED1x3600/4800 K364 T840	1220	70	77	3600/ 4800	30/ 40	120	80+	4000	1,8
Castor LED1x5040/7200 K365 T840	1523	70	77	5040/ 7200	42/ 60	120	80+	4000	2,2

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T840	Colour temperature 4000K, CRI 80+	EM3A	Emergency version equipped with an autonomous testing system, 3 hours
DALI	Driver with DALI interface	EM3D	Emergency version 3 hours with DALI interface
MW	Integrated microwave (MW) motion sensor with on-off control	CBF3x1.5-N m	Outgoing flexible cable 3x1.5mm ² , length according to customer specification
EM3	Emergency version 3 hours	CBF5x1.5-N m	Outgoing flexible cable 5x1.5mm ² , length according to customer specification

STANDARD

