

Gaminio duomenų lentelė

Specifikacijos



impulse relay, Acti9 iTLK, 1NO, 16A, 230V, coil 230V, AC, 50Hz

A9C45116

Main

Range of product	Acti9
Product name	Acti9 iTLK
Product or component type	Impulse relay
Device short name	iTLK
Device application	Standard
Poles	1P
Pole contact composition	1 NO
[In] rated current	16 A
Network type	AC
[Uc] control circuit voltage	230...240 V AC 50/60 Hz 110 V DC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50/60 Hz
Control type	Remote and manual control Coil disconnection
Control signal type	Impulse
Switching frequency	100 switching operations/day 5 switching operations/minute
Impulse duration	50 ms...1 s
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Electrical durability	AC-21 150000 cycles AC-22 100000 cycles

Connections - terminals	Control circuit tunnel type terminals 1 0,5...4 mm ² rigid Control circuit tunnel type terminals 1 0,5...4 mm ² rigid with cable end Control circuit tunnel type terminals 1 1...4 mm ² flexible Control circuit tunnel type terminals 1 1...4 mm ² flexible with ferrule Power circuit tunnel type terminals 1 1,5...4 mm ² rigid Power circuit tunnel type terminals 1 1,5...4 mm ² rigid with cable end Power circuit tunnel type terminals 1 1,5...4 mm ² flexible Power circuit tunnel type terminals 1 1,5...4 mm ² flexible with ferrule
--------------------------------	--

Wire stripping length	11 mm
------------------------------	-------

Tightening torque	1 N.m
--------------------------	-------

Environment

Standards	EN 60929-2-2 EN 60929-1
------------------	----------------------------

Product certifications	GOST
-------------------------------	------

Quality labels	NF VDE IMQ CEBEC KEMA
-----------------------	-----------------------------------

Noise level	60 dB
--------------------	-------

IP degree of protection	IP20 IEC 60529 on opening) IP40 IEC 60529 in enclosure)
--------------------------------	--

Pollution degree	3
-------------------------	---

Tropicalisation	2
------------------------	---

Relative humidity	95 % 55 °C
--------------------------	------------

Ambient air temperature for operation	-20...50 °C
--	-------------

Ambient air temperature for storage	-40...70 °C
--	-------------

Pakavimo vienetai

Pirmos pakuotės vieneto tipas	PCE
--------------------------------------	-----

Vienetų skaičius 1 pakuotėje	1
-------------------------------------	---

1-os pakuotės aukštis	2,0 cm
------------------------------	--------

1-os pakuotės plotis	7,5 cm
-----------------------------	--------

1-os pakuotės ilgis	8,5 cm
----------------------------	--------

1-os pakuotės svoris	103,0 g
-----------------------------	---------

Antros pakuotės vieneto tipas	BB1
--------------------------------------	-----

Vienetų skaičius 2 pakuotėje	12
-------------------------------------	----

2-os pakuotės aukštis	8,5 cm
------------------------------	--------

Package 2 Width	9,5 cm
------------------------	--------

2-os pakuotės ilgis	22,5 cm
----------------------------	---------

2-os pakuotės svoris	1,297 kg
-----------------------------	----------

Trečios pakuotės vieneto tipas	S03
---------------------------------------	-----

Vienetų skaičius 3 pakuotėje	96
-------------------------------------	----

3-ios pakuotės aukštis	30,0 cm
-------------------------------	---------

3-ios pakuotės plotis	30,0 cm
------------------------------	---------

3-ios pakuotės ilgis	40,0 cm
-----------------------------	---------

3-ios pakuotės svoris	10,807 kg
------------------------------	-----------

Offer Sustainability

Tvaraus pasiūlymo statusas	„Green Premium“ gaminys
REACH direktyva	REACH deklaracija
ES RoHS direktyva	Atitinka ES RoHS deklaracija
Be gyvsidabrio	Taip
Kinijos RoHS direktyva	Kinijos RoHS deklaracija Produktas neįeina į Kinijos RoHS apimtį. Medžiagų deklaracija pateikiama jūsų informacijai.
RoHS išimčių informacija	Taip
Aplinkosauginės informacijos atskleidimas	Produkto aplinkosaugos profilis
WEEE	Šį produktą Europos Sąjungos rinkose reikia utilizuoti perduodant į specialias surinkimo vietas ir negalima išmesti su buitineis atliekomis.

Rekomenduojamas (-i) pakeitimas (-ai)