

BEGA**50 133**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

Open and free-radiating wall luminaire · indoor luminaire with hand-blown opal glass and metal bracket.

The character of the opal glass creates a smooth and uniform light distribution in the room.

Product description

Aluminium fitter, finish Colour white
 Stainless steel glass holding bolts
 Hand-blown opal glass
 3 fixing holes \varnothing 6.5 mm
 180 x 240 mm spacing
 2 cable entries for through-wiring for mains cable up to \varnothing 10,5 mm max. $3 \times 1.5^{\square}$
 Connection terminal 2.5^{\square}
 Earth conductor connection
 LED module for power supply
 Suitable for phase angle or phase section dimming
 220-230 V \sim 50/60 Hz
 BEGA Thermal Switch®
 Temporary thermal shutdown to protect temperature-sensitive components
 Safety class I
 – Safety mark
 – Conformity mark
 Weight: 1.8 kg
 This product contains light sources of energy efficiency class(es) F

Lamp

Luminaire connected wattage 28 W
 Rated temperature $t_a = 25^{\circ}\text{C}$
 Ambient temperature $t_{a \text{ max}} = 25^{\circ}\text{C}$

50 133 K3

Module designation 2x LED-1246/930
 Colour temperature 3000 K
 Colour rendering index $R_a > 90$
 Module luminous flux 2640 lm
 Luminaire luminous flux 2252 lm
 Luminaire luminous efficiency 80,4 lm/W

Service life · Ambient temperature

Rated temperature $t_a = 25^{\circ}\text{C}$
 LED module: 79,000h (L80 B50)

Ambient temperature max. $t_a = 25^{\circ}\text{C}$ (100 %)
 LED module: 79,000h (L80 B50)

