

BEGA**50 313**

Ceiling and wall luminaire for indoor use

Project · Reference number

Date

Product data sheet**Application**

Ceiling and wall luminaire · indoor luminaire made of hand-blown opal glass and metal housing, for all lighting tasks. They are ideal for places where a soft and uniform lighting distribution is required. Luminaire with motion sensor.

Product description

Metal housing, finish Colour white
 Hand-blown opal glass, satin matt
 Integrated HF-motion sensor,
 maximum range 10 m
 2 mounting holes \varnothing 6 mm
 Distance apart 230 mm
 2 cable entries for through-wiring for mains
 cable up to \varnothing 10.5 mm max. 3×1.5^2
 Connection terminal 2.5^2
 Earth conductor connection
 LED power supply unit
 230 V \sim 50 Hz
 BEGA Thermal Switch®
 Temporary thermal shutdown to protect
 temperature-sensitive components
 Safety class I
 Impact strength IK03
 Protection against mechanical
 impacts < 0.35 joule
CE – Conformity mark
 Weight: 3.6 kg
 This product contains light sources of energy
 efficiency class(es) D

Inrush current

Inrush current: 20 A / 400 μ s
 Maximum number of luminaires of this
 type per miniature circuit breaker:
 B10A: 9 luminaires
 B16A: 15 luminaires
 C10A: 15 luminaires
 C16A: 25 luminaires

Lamp



Module connected wattage	23.1 W
Luminaire connected wattage	27.7 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \max} = 40$ °C

50 313 K27

Colour temperature	2700 K
Colour rendering index	CRI > 90
Module luminous flux	3710 lm
Luminaire luminous flux	2679 lm
Luminaire luminous efficiency	96,7 lm/W

50 313 K3

Colour temperature	3000 K
Colour rendering index	CRI > 90
Module luminous flux	3760 lm
Luminaire luminous flux	2716 lm
Luminaire luminous efficiency	98,1 lm/W

**Service life · Ambient temperature**

Rated temperature $t_a = 25$ °C	
LED psu:	> 50,000h
LED module:	> 200,000h (L80B50)
	50,000h (L90B50)
Ambient temperature max. $t_a = 40$ °C (100 %)	
LED psu:	50,000h
LED module:	116,000h (L80B50)
	50,000h (L90B50)

Accessory · Trim frames

For this luminaire metal trim frames in 3 enamel surfaces are optional available. Trim frames are accessories and must be ordered separately.

Colour white**Colour palladium****Colour glossy silver**

Part. No

13 137**13 138****13 139****Article No. 50 313**

Colour temperature 2700 K.
 Also available with 3000 K on request.
 2700 K – article number + **K27**
 3000 K – article number + **K3**

If the article number is followed by a **P**, we can also supply these luminaires in impact-resistant synthetic material.