

Product data sheet



NILOÉ STEP LEGRAND

Niloé Step one-way switch, automatic terminals, mechanism with aluminium rocker

REF. 863301 | EAN. 3414971836747

The Niloé Step one-way switch allows to control - switch ON and OFF - the light. The mechanism should be completed with a plate.

> [The product details page](#)

Pagrindinis aprašymas:

The Niloé Step one-way switch allows to control - switch ON and OFF - the light. The mechanism should be completed with a plate.

Produkto savybės:

- Automatic terminals for quick wire connection without tools.
- Mechanism with claws to ease the mounting in case of refurbishment.
- 10AX, 250V~
- Plastic support frame with good rigidity and high resistance.

Rekomendacijos / apribojimai

- To be used indoor only.

Produkto privalumai

Įrengimo privalumai

- Slot system allows a perfect and easy multigang setting. The support frames can be perfectly joined thereby easing the installation.

Naudojimo privalumai

- Allows to control - switch ON and OFF - the light. The mechanism should be completed with a plate.

Unikalios savybės

- Matt aluminium finishing

Techinės charakteristikos

Wiring system	Off switch 1-pole
Method of operation	Rocker/button
Assembly arrangement	Basic element with central cover plate
Number of modules (module system)	10
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Mounting with claw
With mounting plate	Yes

Rated current	10 A
Switching current for fluorescent lamps	10 AX
Feedback-signal contact	No
Connection type	Other
Heating switch	No
Washing machine switch	No
Device width	75.8 mm
Device height	75.8 mm
Device depth	44.8 mm

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Matt
Colour	Aluminium
RAL-number (similar)	9040
Colour of switch operator	Aluminium
Label space/information surface	No
Illumination	Optional
Type of lighting	Other
Suitable for degree of protection (IP)	IP20
Degree of impact strength (IK)	IK04
Nominal voltage	250 V

Built-in depth	31 mm
Min. depth of built-in installation box	31 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature	-5-40 °C
Storage temperature	-10-70 °C
Voltage type	AC
Frequency	50-60 Hz
Terminal marking indication	No
Terminals capacity	1.5-2.5 mm ²
Cable nature for connection	Not applicable
Tube diameter for wall mounted product	58-58 mm

Dokumentacija

Sutartys ir sertifikatai

→ [OC / CB-HU-003437](#) | (0.65Mo)