

# Product data sheet

## Cinch Audio (RCA) / Composite Video



### Reference number

MA LS 1031 WW

### Cinch Audio (RCA) / Composite Video

with supporting frame, screw fixing only

### Spare part:

adapter 4 ref.-no.: MA 1000 AD 4

### Technical data

#### Technical data Cinch Audio (RCA)

Rated voltage:	DC 50 V
Frequency range:	20 Hz ... {2} kHz
Contact resistance:	≤ 20 mΩ
Insulation resistance:	≥ 100 MΩ
Electric strength:	AC 500 V ~ (50/60 Hz) at 1 min 2 mA
Insertion and removal forces:	3 ... 25 N
Insertion/removal cycles:	≥ 1000
Terminal:	white (left) 180° red (right) 180°
Contact material:	gold-plated
Installation depth:	14 mm
Ambient temperature:	-5 ... +45 °C
Installation note:	Installation into deep wall box

#### Technical data Composite Video

Rated voltage:	DC 50 V
Frequency range:	≤ 160 MHz
Contact resistance:	≤ 20 mΩ
Insulation resistance:	≥ 100 MΩ
Electric strength:	AC 500 V ~ (50/60 Hz) at 1 min 2 mA
Insertion and removal forces:	3 ... 25 N
Insertion/removal cycles:	≥ 1000
Terminal:	yellow 180°
Contact material:	gold-plated
Installation depth:	14 mm
Ambient temperature:	-5 ... +45 °C
Installation note:	Installation into deep wall box

### Thermoplastic (breakproof) high-gloss

#### Colour:

white

#### Material:

thermoplastic