

Product data sheet

Specifications

Acti9 - comb busbar - 1L+N with Aux and Vigi - 9 mm pitch - 56 modules



A9N21037

Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L + N
Length in 18 mm modules	56

Complementary

Number of ways	22 ways Aux + N + 1 L + Vigi
Poles configuration for 1 way	1 x 1P + N
Connection pitch	9 mm between phase and neutral
Connector type	Tooth
Distance between way	45 mm
Marking	N L
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	112
Width	1000 mm
Colour	Light grey (RAL 7035)
Range compatibility	Acti 9 C40 Acti 9 C40 Vigi Acti 9 DT40 Acti 9 DT40 Vigi Acti 9 iDPN Acti9 iDPN Vigi Acti9 ID C40 Acti9 IDc Acti9 ITG40 Multi 9 N40 Vigi

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	490 g
Package 1 Height	3 cm
Package 1 width	5 cm
Package 1 Length	97.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	40
Package 2 Weight	34.152 kg
Package 2 Height	112 cm
Package 2 width	80 cm
Package 2 Length	120 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	2.769 kg
Package 3 Height	107 cm
Package 3 width	10 cm
Package 3 Length	10 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------