

Technical Datasheet

Page: 1 / 1

PPSTK19 CS rubber plug, grey

- Material connector housing PP (Polypropylen)
- Material plug cap TPE (Elastomer)
- Rated voltage: 250V AC
- Rated current: 16A AC
- Type of construction acc. DIN 49441 - 2 - AR2
- Conductor cross-section of the connection cable 0.75 to 2.5mm²
- Terminal type: screw terminal; reconnectable
- Number of poles: 2 + PE
- Protective contact: Version with two protective contact systems
- Strain relief: Pressure piece with 2 screws max.
- Torque for connection screws: 0.4 Nm max.
- Torque for strain relief: 0.5 Nm
- Jacket stripping length: 75mm to 80mm
- Wire stripping length: 7mm
- Test mark: VDE, ÖVE, NF, CEBEC
- Certified according to DIN ISO 9001
- Hint:
 - When connecting the cable , make sure that the wire insulation is not clamped
 - Before closing the plug housings, check the fixed position of the cables in the connection terminals and make sure that no cable is clamped between the housing parts
 - Tighten the locking screw of the rubber cap and inner cage until the screw head dips into the rubber cap



Information

Art.-No.	ID-No.	Type	VPE	Colour
05105815	056488	PPSTK19	1	grey