


Gaminio duomenų lentelė

Specifikacijos



Easy UPS 3M 80kVA 400V 3:3 UPS, 6 internal 9Ah modular battery strings, Start-up 5x8

E3MUPS80KHB2S

Apžvalga

Pristatymas	Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 80 kVA, 400V 3-phase UPS. With advanced product features, robust electrical specifications and compact design, the Easy UPS 3M UPS makes business continuity easy for small and medium data centers and other business critical applications. Includes 5x8 start-up service and 6 internal 9Ah modular battery strings.
Pristatymo laikas	Usually Ships within 6 Weeks

Main

Main Input Voltage	3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	80000 W
Rated power in VA	80000 VA
Battery type	VRLA
Provided equipment	Dust filter Installation guide Start-up service

Physical

Colour	White RAL 9003)
Height	197 cm
Width	60 cm
Depth	100 cm
Net weight	879 kg
USB compatible	Yes

Input

Maximum input current	146 A
Max short time withstand current	10 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.5 leading to 0.5 lagging without derating

Input Power Factor at Full Load	0,99
Input voltage limits	342...477 V
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Network frequency	40...70 Hz

Output

Maximum configurable power in VA	80000 VA
Maximum configurable power in W	80000 W
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic distortion	Less than 3 %
Output harmonic distortion	< 3% linear load and < 5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Built-in static bypass

Conformance

Product certifications	CE EAC RCM
Standards	IEC 62040-1-1 IEC 62040-2 IEC 62040-3 ISTA 2B

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...1500 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0,00...4572,00 m
Acoustic level	65 dBA
Heat dissipation	14850 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery voltage	240 V
Number of battery filled slots	0
Number of battery free slots	0
Max current discharge	222 A

Communications & Management

Alarm	Audible and visible alarms prioritized by severity
-------	--

Control panel	Touch screen LCD user interface
---------------	---------------------------------

Pakavimo vienetai

1 pakuotės svoris	387 kg
1 pakuotės aukštis	210,2 cm
1 pakuotės plotis	75 cm
1 pakuotės ilgis	112,5 cm

Offer Sustainability

REACH direktyva	REACH deklaracija
REACH be SVHC	Taip
ES RoHS direktyva	Atitinka ES RoHS deklaracija
Be gyvsidabrio	Taip
RoHS išimčių informacija	Taip
Kinijos RoHS direktyva	Kinijos RoHS deklaracija Produktas neįeina į Kinijos RoHS apimtį. Medžiagų deklaracija pateikiama jūsų informacijai.

Contractual warranty

Garantija	1 year on-site repair or replace with factory authorized Start-Up
-----------	---