



Small, fine, elegant and discreet - The ACAMAR is a light manufactured from high-quality aluminium. The colour reproduction value is over 90, which means high colour authenticity. The design is chic and attractive thanks to its curvature on one side. You can mount the light with the curvature upwards or downwards, depending on your preference. The white paint inside accentuates the warm white light and ensures pleasant scattering upwards and downwards. The outside is highly polished for an incredible shine.

Housing Material	Aluminium	IP Protection Class	IP 20
Housing Color	Black	Life Time L70 / B50	55000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	100000
Rated Input	6.9 W	Power Consumption	7 kWh/1000h
Rated Power Consumption Standby	0.5 W	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class F.
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Dimmable	Yes		
Control	Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	3 SDCM		
CRI (Ra)	92		
Rated Luminous Flux	300 lm		
Rated Angle of Reflection	105 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Length	170 mm		
Width	100 mm		
Height	80 mm		
Base length	120 mm		
Base width	60 mm		
Base height	33 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 60 °C		