



Versatile and functional - The Mensae LED outside wall and ceiling light boasts an impressive flat design and can be used both indoors and outdoors with its movement sensor including daylight sensor. The white cover atop the dark grey aluminium die-cast frame houses 96 warm white LEDs with 18 watts and 3,000 K.

Special features

- Corridor function
- Adjustable motion detector [hold time / detection area]
- Daylight sensor

Housing Material	Aluminium
Housing Color	Dark grey
Material of Lens	Polycarbonate - PC
Protection Class	Protection class I/ protective grounding
Rated Input	16 W
Rated Power Consumption Standby	0.3 W
Rated Power Consumption Network Standby	0.5 W
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	High frequency
Detection Distance	9-12 m
Angle of Detection	120 Degree
Motion detector changeable	Yes
Adjustable brightness threshold	Yes
Brightness threshold	150-1500 lx
Adjustable follow-up time	Yes
Follow-up time	1-3 min

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	80
Rated Luminous Flux	1400 lm
Rated Angle of Reflection	115 Degree
UGR	10

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top, Below, Side

Length	300 mm
Width	300 mm
Height	54 mm
Base height	28.5 mm
Base diameter	170 mm
Working Temperature	-25 to 45 °C
Storage Temperature	-30 to 55 °C
IP Protection Class	IP 65
IK Protection Class	IK08

Life Time L70 / B50	75000 h
Life Time L80 / B10	50000 h
Life Time L80 / B50	60000 h
Switching Cycles	50000
Power Consumption	16 kWh/1000h
Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class D.