



The CETI recessed ceiling light with its LED light sources produces a glare-free, warm white light (3,000 K). The recessed reflectors of the luminaire make a major contribution to this. The interchangeable colored reflector inserts in silver and gold offer additional design options. The CETI can be individually combined with a power supply unit and dimmed.

Special features

- Very low glare light
- Recessed reflectors
- Replaceable coloured reflector inserts
- Can be combined with a power supply unit as desired [excl.]

Housing Material	Aluminium
Housing Color	White
Surface structure	Matt
Material of Lens	Plastic
Surface Structure of Lens	Transparent
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	10.5 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	14-15 V/DC
Rated Current	700 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Cable Length	0.5 m
Dimmable	Yes
Control	Dimmable via optional power supply unit
Motion Detector	No

Length	137 mm
Width	52 mm
Height	44 mm
Installation Depth	50 mm
Cut Out Length	130 mm
Cut Out Width	36 mm
Product weight	240 g

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	11 kWh/1000h
EEL	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	90
Rated Luminous Flux	800 lm
Luminous Efficiency	76.2 lm/W
Rated Angle of Reflection	45 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

