



The CETI recessed ceiling light with its LED light sources produces a glare-free, warm white light (3,000 K). The recessed reflectors of the luminaire make a major contribution to this. The interchangeable colored reflector inserts in silver and gold offer additional design options. The CETI can be individually combined with a power supply unit and dimmed.

Special features

- Very low glare light
- Recessed reflectors
- Replaceable coloured reflector inserts
- Can be combined with a power supply unit as desired [excl.]

Housing Material	Aluminium
Housing Color	White
Surface structure	Matt
Material of Lens	Plastic
Surface Structure of Lens	Transparent

Protection Class	Protection class III/safety extra-low voltage
-------------------------	---

Operating Mode	Constant current
-----------------------	------------------

Rated Input	20.2 W
--------------------	--------

Rated Power Consumption Standby	0.5 W
--	-------

Rated Input Voltage	28-29 V/DC
----------------------------	------------

Rated Current	700 mA
----------------------	--------

Power Supply Unit incl.	No
--------------------------------	----

Connection Cable Secondary	Yes
-----------------------------------	-----

Secondary Cable Length	0.5 m
-------------------------------	-------

Dimmable	Yes
-----------------	-----

Control	Dimmable via optional power supply unit
----------------	---

Motion Detector	No
------------------------	----

Light Source	LED, Light source not changeable
---------------------	----------------------------------

Color Temperature	3000 K
--------------------------	--------

Colour Consistency	6 SDCM
---------------------------	--------

Colour consistency light source	6 SDCM
--	--------

CRI (Ra)	90
-----------------	----

Rated Luminous Flux	1600 lm
----------------------------	---------

Luminous Efficiency	79.2 lm/W
----------------------------	-----------

Rated Angle of Reflection	45 Degree
----------------------------------	-----------

Light Distribution	Symmetric
---------------------------	-----------

Distribution Characteristic 120°	DLS
---	-----

Light Exit Surfaces	1
----------------------------	---

Light characteristics	Direct
------------------------------	--------

Light direction	Below
------------------------	-------

Length	257 mm
Width	52 mm
Height	44 mm
Installation Depth	50 mm
Cut Out Length	250 mm
Cut Out Width	36 mm
Product weight	500 g

Working Temperature	-5 to 40 °C
----------------------------	-------------

Storage Temperature	-10 to 40 °C
----------------------------	--------------

IP Protection Class	IP 20
----------------------------	-------

Life Time L70 / B50	30000 h
----------------------------	---------

Switching Cycles	15000
-------------------------	-------

Power Consumption	21 kWh/1000h
--------------------------	--------------

EEL	G
------------	---

