



Whilst flat surfaces and covers are the go-to for most surface-mounted ceiling lights, the ZANIAH places special emphasis on its 360° lamp [either a 12 W, 18 W or 24 W variant]. Replaceable covers allow the visual appearance of ZANIAH to be changed even after installation. The covers are available in eight colour variants, allowing plenty of scope for customisation.

**Special features**

- Can be customised using coloured covers
- 360° light emission angle
- Can be used as a wall or ceiling light

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Yellow
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	24 W
<b>Rated Power Consumption Standby</b>	0.5 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No

<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	25000
<b>Power Consumption</b>	24 kWh/1000h
<b>EEI</b>	F

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	2565 lm
<b>Rated Angle of Reflection</b>	120 Degree
<b>Distribution Characteristic 120°</b>	NDLS

<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct, Indirect
<b>Light direction</b>	Below, Rear

<b>Height</b>	46 mm
<b>Diameter</b>	420 mm

<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 20
<b>IK Protection Class</b>	IK05