



Modular, compact, impactful - The GRUMIUM wall-mounted light can be installed on patios, building walls or in entrances to living spaces and, thanks to its optional covers in different designs, provides a flexible universal solution for many areas of application. The permanently installed and energy-saving LEDs delivering max. 10 watts are encompassed by a diffuser made of milky plastic and produce a pleasant warm white light with a luminous flux of 730 lm. The Grumium outdoor light with die-cast aluminium housing comes in an angular and rounded design and has degree of protection IP54.

<b>Housing Material</b>	Aluminium	<b>Storage Temperature</b>	-10 to 60 °C
<b>Housing Color</b>	Dark grey	<b>IP Protection Class</b>	IP 54
<b>Material of Lens</b>	Plastic	<b>Life Time L70 / B50</b>	30000 h
<b>Colour of Lens</b>	White	<b>Switching Cycles</b>	15000
<b>Protection Class</b>	Protection class I/protective grounding	<b>Power Consumption</b>	11 kWh/1000h
<b>Rated Input</b>	10 W	<b>EEL</b>	F
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour consistency light source</b>	6 SDCM		
<b>CRI (Ra)</b>	80		
<b>Rated Luminous Flux</b>	210 lm		
<b>Rated Angle of Reflection</b>	160 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Top, Below, Side		
<b>Length</b>	100 mm		
<b>Width</b>	70 mm		
<b>Height</b>	200 mm		
<b>Base length</b>	95 mm		
<b>Base width</b>	15 mm		
<b>Base height</b>	195 mm		
<b>Working Temperature</b>	-20 to 40 °C		

