



If you're looking for a slim, powerful and flexible three-phase spotlight, look no further than the Horus. The slimline housing and matt surface finish combined with the powerful chip for all wattages make the Horus a true jack-of-all-trades.

**Special features**

- low glare value
- can be rotated and swivelled

|                                         |                                         |
|-----------------------------------------|-----------------------------------------|
| <b>Housing Material</b>                 | Plastic                                 |
| <b>Housing Color</b>                    | White                                   |
| <b>Surface structure</b>                | Matt                                    |
| <b>Material of Lens</b>                 | Plastic                                 |
| <b>Colour of Lens</b>                   | White                                   |
| <b>Functions</b>                        | Phase switch                            |
| <b>Protection Class</b>                 | Protection class I/protective grounding |
| <b>Rated Input</b>                      | 20 W                                    |
| <b>Rated Input Voltage Frequency</b>    | 220-240 V/AC 50 / 60 Hz                 |
| <b>Power Supply Unit incl.</b>          | Yes                                     |
| <b>Dimmable</b>                         | No                                      |
| <b>Motion Detector</b>                  | No                                      |
| <b>Light Source</b>                     | LED, Light source not changeable        |
| <b>Lightcolor</b>                       | Warm white (WW)                         |
| <b>Color Temperature</b>                | 3000 K                                  |
| <b>Colour Consistency</b>               | 6 SDCM                                  |
| <b>Colour consistency light source</b>  | 6 SDCM                                  |
| <b>CRI (Ra)</b>                         | 80                                      |
| <b>Rated Luminous Flux</b>              | 1705 lm                                 |
| <b>Luminous Efficiency</b>              | 85.3 lm/W                               |
| <b>Rated Angle of Reflection</b>        | 40 Degree                               |
| <b>UGR</b>                              | 19                                      |
| <b>Light Distribution</b>               | Symmetric                               |
| <b>Distribution Characteristic 120°</b> | DLS                                     |
| <b>Swivel Angle</b>                     | 350 Degree                              |
| <b>Light Exit Surfaces</b>              | 1                                       |
| <b>Light characteristics</b>            | Direct                                  |
| <b>Light direction</b>                  | Below                                   |
| <b>Height</b>                           | 185 mm                                  |
| <b>Diameter</b>                         | 80 mm                                   |

|                              |                   |
|------------------------------|-------------------|
| <b>Product weight</b>        | 651 g             |
| <b>Working Temperature</b>   | -20 to 40 °C      |
| <b>Storage Temperature</b>   | -20 to 40 °C      |
| <b>IP Protection Class</b>   | IP 20             |
| <b>Life Time L70 / B50</b>   | 54000 h           |
| <b>Switching Cycles</b>      | 30000             |
| <b>Power Consumption EEI</b> | 20 kWh/1000h<br>F |

