



If you're looking for a slim, powerful and flexible three-phase spotlight, look no further than the Horus. The slimline housing and matt surface finish combined with the powerful chip for all wattages make the Horus a true jack-of-all-trades.

Special features

- low glare value
- can be rotated and swivelled

Housing Material	Plastic
Housing Color	Black
Surface structure	Matt
Material of Lens	Plastic
Functions	Phase switch
Protection Class	Protection class I/protective grounding
Rated Input	30 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	No
Light Source	LED, Light source not changeable
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	80
Rated Luminous Flux	2605 lm
Luminous Efficiency	86.8 lm/W
Rated Angle of Reflection	40 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS
Swivel Angle	350 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Height	210 mm
Diameter	90 mm
Product weight	941 g

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	54000 h
Switching Cycles	30000
Power Consumption	30 kWh/1000h
EEL	F

