

**Special features**

- Including 0.5 m connecting cable with protected connection socket

Housing Material	Stainless steel, Aluminium
Housing Color	Silver
Material of Lens	Glass
Functions	Walkable - 5 kN
Protection Class	Protection class II/protective insulation
Rated Input	2 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box IP67
Dimmable	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	5 SDCM
Colour consistency light source	5 SDCM
CRI (Ra)	80
Rated Luminous Flux	150 lm
Luminous Efficiency	75 lm/W
Rated Angle of Reflection	30 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	43 mm
Diameter	58 mm
Installation Depth	48 mm
Cut Out Diameter	44 mm
Product weight	339 g

Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
IK Protection Class	IK08
Load Force max.	5 kN

Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption EEI	3 kWh/1000h G