

**Special features**

- Including 1 m connecting cable with WEIPU plug

Housing Material	Stainless steel, Aluminium
Housing Color	Silver
Material of Lens	Glass
Functions	Driveable - 20 kN
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	2.4 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Primary Connection	WEIPU plug 2-pole
Primary Cable Length	1 m
Connection Cable Secondary	Yes
Dimmable	Yes
Control	Dimmable via optional controller
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	80
Rated Luminous Flux	180 lm
Luminous Efficiency	75 lm/W
Rated Angle of Reflection	30 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	82.5 mm
---------------	---------

Diameter	55 mm
Installation Depth	98 mm
Cut Out Diameter	48 mm
Product weight	428 g
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	20 kN
Life Time L70 / B50	25000 h
Switching Cycles	15000
Power Consumption EEI	3 kWh/1000h G