



**Special features**

- Incl. four heavy-duty anchors

|   |   |                            |             |
|---|---|----------------------------|-------------|
| <b>Housing Material</b>                 | Aluminium                               | <b>Life Time L70 / B50</b> | 30000 h     |
| <b>Housing Color</b>                    | Dark grey                               | <b>Switching Cycles</b>    | 15000       |
| <b>Material of Lens</b>                 | Plastic                                 | <b>Power Consumption</b>   | 3 kWh/1000h |
| <b>Protection Class</b>                 | Protection class I/protective grounding |                            |             |
| <b>Rated Input</b>                      | 2.5 W                                   |                            |             |
| <b>Rated Input Voltage Frequency</b>    | 220-240 V/AC 50 / 60 Hz                 |                            |             |
| <b>Power Supply Unit incl.</b>          | Yes                                     |                            |             |
| <b>Dimmable</b>                         | No                                      |                            |             |
| <b>Motion Detector</b>                  | No                                      |                            |             |
| <b>Light Source</b>                     | LED, Light source not changeable        |                            |             |
| <b>Color Temperature</b>                | 3000 K                                  |                            |             |
| <b>Colour Consistency</b>               | 6 SDCM                                  |                            |             |
| <b>Colour consistency light source</b>  | 6 SDCM                                  |                            |             |
| <b>CRI (Ra)</b>                         | 80                                      |                            |             |
| <b>Rated Luminous Flux</b>              | 34 lm                                   |                            |             |
| <b>Rated Angle of Reflection</b>        | 60 Degree                               |                            |             |
| <b>Distribution Characteristic 120°</b> | DLS                                     |                            |             |
| <b>Light Exit Surfaces</b>              | 1                                       |                            |             |
| <b>Light characteristics</b>            | Indirect                                |                            |             |
| <b>Light direction</b>                  | Side                                    |                            |             |
| <b>Height</b>                           | 54 mm                                   |                            |             |
| <b>Diameter</b>                         | 210 mm                                  |                            |             |
| <b>Base height</b>                      | 7 mm                                    |                            |             |
| <b>Base diameter</b>                    | 198 mm                                  |                            |             |
| <b>Working Temperature</b>              | -20 to 40 °C                            |                            |             |
| <b>Storage Temperature</b>              | -30 to 50 °C                            |                            |             |
| <b>IP Protection Class</b>              | IP 67                                   |                            |             |
| <b>IK Protection Class</b>              | IK10                                    |                            |             |