



Special features

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection

| | |
|-----------------------------|---|
| Housing Material | Plastic |
| Housing Color | Black |
| Operating Mode | Constant current |
| Protection Class | Protection class II/protective insulation |
| Power | 7.0-12 W |
| Output Voltage | 10-17 V/DC |
| Output Current | 700 mA |
| Dimmable | Yes |
| Control | Trailing-edge dimmer |
| Number of Channels | 1 |
| Power Factor | 0.95 |
| Primary Connection | With free strand / conductor ends |
| Secondary Connection | Open cables |

| | |
|-------------------------------|--------------|
| Max. units per MCB B10 | 35 |
| Max. units per MCB B16 | 56 |
| Max. units per MCB C10 | 74 |
| Max. units per MCB C16 | 118 |
| Inrush Current max. | 5 A / 300 µs |
| Capacitive Load | 188 µF |
| Reference Point Tc | 90 °C |
| Working Temperature | -20 to 50 °C |
| Storage Temperature | -20 to 70 °C |
| IP Protection Class | IP 65 |

Life Time 30000 h

| | |
|-----------------------|--------|
| Length | 50 mm |
| Width | 48 mm |
| Height | 24 mm |
| Product weight | 89.3 g |

