



Special features

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Housing Material	Aluminium	Base length	40 mm
Housing Color	White	Base width	80 mm
Material of Lens	Glass	Base height	130 mm
Colour of Lens	Clear	Working Temperature	-20 to 45 °C
Surface Structure of Lens	Clear	Storage Temperature	-20 to 45 °C
Functions	Nightsaver, Seawater resistant	IP Protection Class	IP 65
Protection Class	Protection class I/protective grounding	IK Protection Class	IK08
Rated Input	33 W	Life Time L70 / B50	50000 h
Rated Power Consumption Standby	0.5 W	Switching Cycles	100000
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Power Consumption	33 kWh/1000h
Power Supply Unit incl.	Yes	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Number of Cable Entries	2 PCS		
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Voltage range DC	176-250 V/DC		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	4 SDCM		
Colour consistency light source	3 SDCM		
CRI (Ra)	92		
Rated Luminous Flux	3100/3400 lm		
Rated Angle of Reflection	36 Degree		
UGR	16		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	218 mm		
Diameter	140 mm		