



Special features

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Housing Material	Aluminium	Height	332 mm
Housing Color	White	Base length	44.5 mm
Material of Lens	Glass	Base width	80 mm
Colour of Lens	Clear	Base height	130 mm
Surface Structure of Lens	Clear	Working Temperature	-20 to 45 °C
Functions	Seawater resistant	Storage Temperature	-20 to 60 °C
Protection Class	Protection class I/protective grounding	IP Protection Class	IP 65
Rated Input	55 W	IK Protection Class	IK08
Rated Power Consumption Standby	0.5 W	Life Time L70 / B50	50000 h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Switching Cycles	100000
Power Supply Unit incl.	Yes	Power Consumption	55 kWh/1000h
Number of Cable Entries	2 PCS	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Voltage range DC	176-250 V/DC		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	4 SDCM		
Colour consistency light source	3 SDCM		
CRI (Ra)	90		
Rated Luminous Flux	5400/5800 lm		
Rated Angle of Reflection	36 Degree		
UGR	12		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Length	140 mm		
Width	140 mm		