



Special features

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Housing Material	Aluminium	Base height	130 mm
Housing Color	Light grey	Working Temperature	-20 to 45 °C
Material of Lens	Glass	Storage Temperature	-20 to 60 °C
Colour of Lens	Clear	IP Protection Class	IP 65
Surface Structure of Lens	Clear	IK Protection Class	IK08
Functions	Seawater resistant		
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	50000 h
Rated Input	20 W	Switching Cycles	100000
Rated Power Consumption Standby	0.5 W	Power Consumption	20 kWh/1000h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Power Supply Unit incl.	Yes		
Number of Cable Entries	2 PCS		
Dimmable	Yes		
Control	Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	4 SDCM		
Colour consistency light source	3 SDCM		
CRI (Ra)	92		
Rated Luminous Flux	1700/1900 lm		
Rated Angle of Reflection	36 Degree		
UGR	19		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Height	238 mm		
Diameter	100 mm		
Base length	40 mm		
Base width	80 mm		