



#### Special features

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

<b>Housing Material</b>	Aluminium	<b>Base height</b>	130 mm
<b>Housing Color</b>	Dark grey	<b>Working Temperature</b>	-20 to 45 °C
<b>Material of Lens</b>	Glass	<b>Storage Temperature</b>	-20 to 60 °C
<b>Colour of Lens</b>	Clear	<b>IP Protection Class</b>	IP 65
<b>Surface Structure of Lens</b>	Clear	<b>IK Protection Class</b>	IK08
<b>Functions</b>	Nightsaver, Seawater resistant	<b>Life Time L70 / B50</b>	50000 h
<b>Protection Class</b>	Protection class I/protective grounding	<b>Switching Cycles</b>	100000
<b>Rated Input</b>	6 W	<b>Power Consumption</b>	6 kWh/1000h
<b>Rated Power Consumption Standby</b>	0.5 W	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class E.
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Number of Cable Entries</b>	2 PCS		
<b>Dimmable</b>	Yes		
<b>Control</b>	Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	4 SDCM		
<b>Colour consistency light source</b>	3 SDCM		
<b>CRI (Ra)</b>	90		
<b>Rated Luminous Flux</b>	480/550 lm		
<b>Rated Angle of Reflection</b>	30 Degree		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Length</b>	70 mm		
<b>Width</b>	70 mm		
<b>Height</b>	150 mm		
<b>Base length</b>	43 mm		
<b>Base width</b>	55 mm		