

Product data sheet

LED spotlight Plug & Light



Reference number

PL S1 D05 SW SW

LED spotlight Plug & Light

for power supply Plug & Light, ref.-no.: PL 08 U

Intended use

- Dimmable light attachment for indoor lighting
- Wall or ceiling mounting by plugging onto the light socket of the Plug & Light system

Product characteristics

- Dimming with suitable LED dimmer at constant colour temperature of 2700 K
- Symmetrical optics, beam angle of 35°
- Flicker-free light over the entire dimming range
- Light attachment can be changed during ongoing operation
- Adjustable anti-glare ring via 3 latch positions (5, 10 and 15 mm)
- Swivelling by 90°
- Stepless rotation through 360°

Technical data

Rated voltage:	DC 12 V SELV
Power consumption:	5.6 W
Connection mode:	electrical coupling via gold-plated sliding contacts
Protection class:	III
Luminous flux:	390 lm
Colour temperature:	2,700 K
Colour rendering index:	typical 85
Beam angle:	35 °
Diameter:	42 mm
Length without anti-glare ring:	80 mm
Length with anti-glare ring:	85 ... 95 mm
Housing material:	aluminium lacquered / plastic
Energy efficiency class:	G
This luminaire contains built-in LED lamps, which cannot be replaced.	



Colour:
black

Material:
thermoplastic