

Product data sheet

Specifications



Renova rocker switch intermediate 16 A 250 V black

WDE011231

Main

Range	Renova
Product or component type	Switch
Device application	Light control
Device presentation	Mechanism with fixing frame
Colour	Black (NCS S 9000-N)
Quantity per set	Set of 5
Switch function	Intermediate

Complementary

Technology type	Electromechanical
Product compatibility	To be completed with Renova frame
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Connections - terminals	Screwless terminals
Number of loop terminals	2
Clamping connection capacity	1 x 1.5...2 x 2.5 mm² for solid cable(s) 1 x 1.5...2 x 2.5 mm² for solid stranded cable(s)
Device mounting	Flush
Switch pattern	[7]
Actuator	Rocker
Material	PC/ABS
Fixing mode	By claws By screws
Diameter	71 mm
Embedding depth	15 mm
Projecting depth	19 mm
IP degree of protection	IP20 also with visual parts removed
Product certifications	NEMKO CE SEMKO FIMKO
Standards	EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	72 g
Package 1 Height	5 cm
Package 1 width	7 cm
Package 1 Length	7 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	1600
Package 2 Weight	172 kg
Package 2 Height	99 cm
Package 2 width	80 cm
Package 2 Length	120 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	403 g
Package 3 Height	10.6 cm
Package 3 width	11.9 cm
Package 3 Length	20 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins